

S.C. Kubitech S.R.L.  
 700268 Iași, Bd. Socola 57, bl. A1, RO 8508803, J22/874/1996  
 T/F: 0232 257.555, contact@kubitech.ro, www.kubitech.ro  
 RO39 BPOS 2400 2831 438R OL01 - Bancpost Iași



**Kubitech**  
 tehnică de frig

**Copeland**

## Agregate cu compresoare semiermetice Discus

### R404A

Model	Interval temp °C	Putere frigorifica Kw		Tensiune de alim. V
		-25 °C	-10 °C	
P8-2DC-50X	-40...+7	3,95	7,90	380/50
R7-2DD-50X	-40...+7	4,90	9,65	380/50
R7-2DL-75X	-40...+7	6,65	12,15	380/50
P8-2DB-50X	-45...-15	7,45	-	380/50
S9-2DB-75X	-40...+7	8,35	14,85	380/50
P8-3DA-50X	-45...-15	7,80	-	380/50
S9-3DA-75X	-40...+7	9,10	16,20	380/50
R7-3DC-75X	-45...-20	9,85	-	380/50
V6-3DC-100X	-40...+7	11,45	20,40	380/50
S9-3DS100X	-45...-20	13,35	-	380/50
V6-3DS-150X	-40...+7	15,20	25,50	380/50
W9-3DS-150X	-40...+7	15,60	26,60	380/50
Z9-4DA-200X	-35...+7	17,40	32,00	380/50
V6-4DL-150X	-45...-20	19,70	-	380/50
Z9-4DH-250X	-35...+7	21,40	38,50	380/50
W9-4DT-220X	-45...-20	22,70	-	380/50

Z9-4DJ-300X	-30...+7	25,30	42,50	380/50
W99-6DH-350X	-30...+7	32,50	55,50	380/50
Z9-6DL-270X	-45...-15	30,00	-	380/50
W99-6DJ-400X	-30...+7	37,00	61,50	380/50
Z9-6DT-300X	-45...-15	34,50	-	380/50

temperatura exterioara: 32°C

versiune motor	voltaj	conexiune
AWM	380/3/50	YYY
EWL	380/3/50	Y