

S.C. Kubitech S.R.L.
700268 Iași, Bd. Socola 57, bl. A1, RO 8508803, J22/874/1996
T/F: 0232 257.555, contact@kubitech.ro, www.kubitech.ro
RO39 BPOS 2400 2831 438R OL01 - Bancpost Iași



Kubitech
tehnică de frig



Agregate semiermetice

R404A

Model	Domeniu de lucru °C	Putere frigorifică* W		Alimentare V	I _{max} A
		-25 °C	-10°C		
LH32/2KC-05.2Y	-40...+5	950	1830	220/380	4,6/2,7
LH32/2JC-07.2Y	-40...0	1270	2670	220/380	6,0/3,5
LH33/2HC-1.2Y	-40...-5	1700	3070	220/380	6,1/3,5
LH33/2HC-2.2Y	-30...+5	1710	3090	220/380	7,4/4,3
LH33/2GC-2.2Y	-40...0	1960	3460	220/380	8,1/4,7
LH44/2GC-2.2Y	-40...+5	2080	3780	220/380	8,1/4,7
LH44/2FC-2.2Y	-40...-5	2460	4310	220/380	8,5/4,9
LH44/2FC-3.2Y	-30...+5	2450	4310	220/380	10,0/5,8
LH44/2EC-2.2Y	-40...-10	2890	4960	220/380	9,9/5,7
LH44/2EL-2.2Y	-40...-10	3040	5230	220/380	9,7/5,6
LH64/2EC-3.2Y	-30...+5	3280	6060	220/380	12,0/6,9
LH64/2EL-3.2Y	-30...+5	3410	6260	220/380	11,3/6,5
LH53/2DC-2.2Y	-40...-10	3440	5920	220/380	11,9/6,9
LH53/2DL-2.2Y	-40...-10	3600	6220	220/380	12/6,9
LH64/2DC-3.2Y	-30...+5	3830	6990	220/380	13,5/7,8
LH64/2DL-3.2Y	-30...+5	3940	7150	220/380	13,8/8,0
LH64/2CC-3.2Y	-40...-10	4620	8310	220/380	14,8/8,5
LH64/2CL-3.2Y	-40...-10	4675	8370	220/380	13,8/8,0
LH64/2U-3.2Y	-40...-10	5460	9610	220/380	16,9/9,6
LH64/2Q-4.2Y	-40...-10	6370	10940	220/380	19,6/11,3
LH84/2CC-4.2Y	-30...+5	4810	8880	220/380	16,4/9,4
LH84/2CL-4.2Y	-30...+5	4870	8890	220/380	15,5/9,0
LH84/2U-5.2Y	-30...+5	5700	10310	220/380	21,6/12,5
LH84/2Q-6.2Y	-30...+5	6710	11940	220/380	23,3/13,5
LH84/2N-5.2Y	-40...-10	8160	14050	220/380	22,9/13,2
LH64/4FC-3.2Y	-40...-10	5080	9040	220/380	15,9/9,2
LH84/4FC-5.2Y	-30...+5	5320	9720	220/380	18,7/10,8
LH64/4EC-4.2Y	-40...-10	6070	10400	220/380	18,5/10,7
LH84/4EC-6.2Y	-30...+5	6430	11380	220/380	22,9/13,2
LH84/4DC-5.2Y	-40...-10	7590	13290	220/380	23,4/13,5
LH104/4DC-7.2Y	-30...+5	7930	14240	220/380	27,5/15,9
LH104/2N-7.2Y	-30...+5	8500	15050	220/380	31,1/18,0
LH84/4CC-6.2Y	-40...-10	8860	14950	220/380	27,5/15,9
LH84/4V-6.2Y	-40...-10	9140	15630	380	14
LH104/4Z-8.2Y	-30...+5	8240	14970	380	17
LH114/4V-10.2Y	-30...+5	9800	17510	380	21
LH104/4T-8.2Y	-40...-10	11450	19540	380	17
LH114/4T-12.2Y	-30...0	11760	20450	380	24

LH114/4P-10.2Y	-40...-10	13450	23150	380	21
LH135/4P-15.2Y	-30...+5	14760	26950	380	31
LH124/4N-12.2Y	-40...-10	16150	27600	380	24
LH135/4N-20.2Y	-30...+5	17180	30600	380	37
LH135/4J-13.2Y	-40...-10	19370	33700	380	27
LH135/4J-22.2Y	-30...+5	18630	33000	380	39
LH135/4H-15.2Y	-40...-10	22100	37700	380	31
LH135/4H-25.2Y	-30...0	21250	37000	380	45
LH135/4G-20.2Y	-40...-10	24800	41600	380	37
LH135/6J-22.2Y	-40...-10	27000	44900	380	39
LH135/6H-25.2Y	-40...-15	30400	-	380	45