

S.C. Kubitech S.R.L.  
700268 Iași, Bd. Socola 57, bl. A1, RO 8508803, J22/874/1996  
T/F: 0232 257.555, contact@kubitech.ro, www.kubitech.ro  
RO39 BPOS 2400 2831 438R OL01 - Bancpost Iași



**Kubitech**  
tehnică de frig



## Separatoare picaturi

Model	D. int. racord mm	Inaltime mm	D. ext. mm	Volum intern dm <sup>3</sup>		
				R134a	R22	R404A
VA 32-5 S	16	314	76	1,37	1,36	1,22
VA 54-7 SRD	22	248	127	2,72	2,72	2,43
VA 57-9 SRD	28	376	127	4,35	4,31	3,85
VA 59-11 SRD	35	468	127	5,49	5,44	4,86
VA 616-13 SRD	42	555	152	9,15	9,07	8,11

- presiune maxima de lucru: 32 bar
- temperatura maxima ambianta: +105°C

**CARLY**

## Separatoare picaturi

Model	Diam. int. racord mm	Inaltime mm	D.racord* mm	D.ext. mm	Vol. int. dm <sup>3</sup>
LCY 25 MMS	16	363	-	102	2,2
LCY 47 MMS	22	487	-	102	3,2
LCY 27 MMS	22	373	-	102	2,2
LCY 49 MMS	28	462	-	121	4,0
LCY 811 MMS	35	554	-	152	7,4
LCY 813 MMS	42	554	-	152	7,1
LCYT 1517 MMS	54	582	-	219	5,0
<b>Cu schimbator de caldura</b>					
LCYE 25 MMS	16	363	10	102	2,2
LCYE 47 MMS	22	487	12	102	3,2
LCYE 69 MMS	28	435	16	152	5,8
LCYE 811 MMS	35	554	16	152	7,4
LCYE 1013 MMS	42	662	18	152	9,2

\* diametrul racordului schimbatorului de caldura

- temperatura de lucru: -50...+100°C

- presiune maxima de lucru: 20 bar

- presiune maxima de lucru pe partea de schimbator de caldura: 35 bar