



Ventile de inchidere cu bila

Model	Cod Danfoss	Conexiune sudat mm	Debit k_v m ³ /h
GBC 6s	9G5030	6	0,8
GBC 10s	9G5031	10	1,6
GBC 12s	9G5032	12	7,6
GBC 16s	9G5023	16	10,4
GBC 18s	9G5035	18	17,5
GBC 22s	9G5025	22	26
GBC 28s	9G5033	28	46
GBC 35s	9G5027	35	55
GBC 42s	9G5034	42	94
GBC 54s	9G5029	54	98

Presiune maxima de lucru: 35 bar

Domeniu de temperatura: -40...+150°C

Temperatura mediului ambiant: -50...+80°C



Ventile de inchidere cu bila

Model	Conexiune sudabil mm	Debit k_v m ³ /h	Diametru bila mm
54A/M 6	6	1,60	10
54A/M 8	8	3,50	10
54A/M10	10	3,50	10
54A/M12	12	3,80	10
54B/M15	15	11,60	15
54B/M16	16	13,00	15
54B/M18	18	13,40	15
54C/M22	22	37,00	20

54D/M28	28	48,30	25
54E/M35	35	84,80	32
54F/M42	42	98,80	40
54G/M54	54	199,60	50
54PL/M64	64	-	50

Presiune maxima de lucru: 34 bar

Temperatura de lucru : -30...+120°C