

S.C. Kubitech S.R.L.
 700268 Iași, Bd. Socola 57, bl. A1, RO 8508803, J22/874/1996
 T/F: 0232 257.555, contact@kubitech.ro, www.kubitech.ro
 RO39 BPOS 2400 2831 438R OL01 - Bancpost Iași



Kubitech
 tehnică de frig



Ventile de reglaj termostatic

R22

Model	Putere nom. kW	Diuza Model	Element termostatic				Corp ventil
			fara MOP	MOP 0°C	MOP -10°C	MOP -18°C	Model
			Model				
TCLE 50HW	1,9	X22440-B1B	XB1019 HW-1B	XB1019 HW100-1B	XB1019 HW65-1B	XB1019 HW35-1B	C501-5MM lip.int.10x16
TCLE 100HW	3,7	X22440-B2B					
TCLE 200HW	7,9	X22440-B3B					
TCLE 250HW	11,9	X22440-B3,5B					
TCLE 300HW	17,3	X22440-B4B					C501-7MM lip.int.12x16
TCLE 500HW	22,2	X22440-B5B					
TCLE 750HW	30,4	X22440-B6B					
TCLE1000HW	41,1	X22440-B7B					A576MM lip.int. 16x22 lip.ext.22x28
TCLE1200HW	47,8	X22440-B8B					
TJRE 14HW	57,7	X11873-B4B					10331 lip.int.22x22 lip.ext.28x28
TJRE 18HW	69,2	X11873-B5B					

TERE 22HW	86,5	X9117-B6B	XC726 HW-2B	XC726 HW100-2B	XC726 HW65-2B	XC726 HW35-2B	9153 lip.int.22x22 lip.ext.28x28
TERE 26HW	102,3	X9117-B7B					
TERE 35HW	137,5	X9117-B8B					
TERE 45HW	177,0	X9117-B9B					
TIRE 55HW	216,3	X9166-B10B					
THRE 75HW	295,0	X9144-B11B					
THRE 100HW	393,0	X9144-B13B					9149 lip.int.22x22 lip.ext.28x28

Temperatura de vaporizare: +30...-45°C

Lungimea capilar: 1,5m (TCLE), 3m (TJRE, TERE, TIRE, THRE)

Temperatura maxima : 7 175 °C fara MOP