

S.C. Kubitech S.R.L.
 700268 Iași, Bd. Socola 57, bl. A1, RO 8508803, J22/874/1996
 T/F: 0232 257.555, contact@kubitech.ro, www.kubitech.ro
 RO39 BPOS 2400 2831 438R OL01 - Bancpost Iași



Kubitech
 tehnică de frig



Ventile de reglaj termostatic

Model	Domeniul de lucru numarul diuzei / conexiuni	Cod Danfoss			
		R134a	R404A	R407C	R22
TE5					
Element termostatic	+10...-40°C, fara MOP	067B3297	067B3342	067B3278	067B3250
	-25...-60°C, fara MOP		067B3344		067B3263
	+10...-40°C, MOP+15°C	067B3298	067B3238	067B3277	067B3267
	-5...-40°C, MOP 0°C	067B3360	067B3357		067B3249
	-15...-40°C, MOP -10°C	067B3327	067B3358		067B3253
	-25...-60°C, MOP -20°C		067B3343		067B3251
Diuza	Nr. Putere in kW*				
	R134a R404A/ R507 R407C/ R22				
	1: 10,3 14,0 20,8	067B2089			
	2: 15,5 20,4 28,3	067B2090			
	3: 22,8 29,5 40,6	067B2091			
4: 32,7 42,2 58,0	067B2092				
	12-16 cu filet-drept	067B4013			
	12-16 sud.-drept ODF	067B4002			

Corp ventil	12-22 sud.-drept ODF	067B4003			
	12-16 sud.-cot 90° ODF	067B4004			
	12-22 sud.-cot 90° ODF	067B4005			
	16-22 sud.-cot 90° ODF	067B4012			
TE12					
Element termostatic	+10...-40°C, fara MOP	067B3232	067B3347	067B3366	067B3210
	+10...-40°C, MOP+15°C			067B3367	067B3227
	-5...-40°C, MOP 0°C		067B3345		067B3207
	-15...-40°C, MOP -10°C		067B3348		067B3213
	-25...-60°C, MOP -20°C		067B3349		067B3211
Diuza	Nr.	Putere in kW*			
		R134a	R404A/	R407C	R22
		R507			
	1:	14,3	14,8	29,9	26,8
	2:	23,3	23,9	47,4	43,5
3:	34,0	35,2	69,3	63,9	
4:	45,5	47,1	91,5	85,0	
Corp ventil	22x28 sud.-drept ODFxODM	067B4016			
	22x28 sud.-cot 90° ODFxODM	067B4017			
	16-22 sud.-drept ODF	067B4018			
	22x25 sud.-cu flanse ODF	067B4015			
TE20					
Element termostatic	+10...-40°C, fara MOP	067B3292	067B3352	067B3371(1)	067B3274
	+10...-40°C, MOP+15°C			067B3372(1)	067B3286
	-5...-40°C, MOP 0°C		067B3351		067B3273
	-15...-40°C, MOP -10°C		067B3353		067B3275
	-25...-60°C, MOP -20°C		067B3354		067B3276
Diuza	Nr.	Putere in kW*			
		R134a	R404A/	R407C	R22
		R507			
1:	57	59	119	107	
Corp ventil	22x28 sud.-drept ODFxODM	067B4016			
	22x28 sud.-cot 90° ODFxODM	067B4017			
	22x25 sud.-cu flanse ODF	067B4015			

(1) lungimea capilarului: 5m



Model	Domeniul de lucru numarul diuzei / conexiuni	Cod Danfoss			
		R134a	R404A	R407C	R22
TE55					
Element termostatic	+10...-40°C, fara MOP	067G3222	067G3302	067G3240(1)	067G3205
	+10...-40°C, MOP+15°C			067G3241(1)	
	-5...-40°C, MOP 0°C		067G3303		067G3206
	-15...-40°C, MOP -10°C		067G3304		
	-25...-60°C, MOP -20°C		067G3305		067G3207
Diuza	Nr.	Putere in kW*			
		R134a	R404A/	R407C	R22
			R507		
	1:	123	130	265	237
	2:	188	197	393	355
Corp ventil	28X35 sud.-drept ODM	067G4001			
	28X35 sud.-cot 90° ODM	067G4002			

(1) lungimea capilarului: 5m