

**S.C. Kubitech S.R.L.**  
700268 Iași, Bd. Socola 57, bl. A1, RO 8508803, J22/874/1996  
T/F: 0232 257.555, contact@kubitech.ro, www.kubitech.ro  
RO39 BPOS 2400 2831 438R OL01 - Bancpost Iași



**Kubitech**  
tehnică de frig



## Ventile închidere cu membrana

Ventil cu membrana cu trecere directă, cu racord cu filet la ambele capete

Model	Conexiuni SAE	Debit $k_v$ m <sup>3</sup> /h	Dimensiuni mm	
			lungime	inaltime
6210/2	1/4"	0,28	58	68
6210/3	3/8"	1,00	74	72
6210/4	1/2"	1,30	78	72
6210/5	5/8"	1,80	78	72
6210/6	1 1/16 UNF	3,65	98	86

**Ventil cu membrana cu trecere directa, cu racord sudabil la ambele capete**

Model	Conexiuni SAE	Debit $k_v$ m <sup>3</sup> /h	Dimensiuni mm	
			lungime	inaltime
6220/0	1/4"	0,28	53	68
6220/3	3/8"	1,00	61	72
6220/4	1/2"	1,30	70	72
6220/5	5/8"	1,80	71	72
6220/6	3/4"	3,65	92	86
6220/7	7/8"	3,65	94	86

**Ventil cu membrana cu racord filetat**

Model	Conexiuni SAE	Debit $k_v$ m <sup>3</sup> /h	Dimensiuni mm	
			lungime	inaltime
6230/22	1/4"	0,50	34	82
6230/33	3/8"	1,40	37	82
6230/44	1/2"	1,60	37	86,5

**Ventil cu trei cai cu membrana, cu racord filetat**

Model	Conexiuni SAE	Debit $k_v$ m <sup>3</sup> /h	Dimensiuni mm	
			lungime	inaltime
6260/2	1/4"	0,35	68	72
6260/3	3/8"	0,90	72	72
6260/4	1/2"	1,35	74	72

Presiune maxima de lucru: 28 bar

Domeniu de lucru: -35...+90°C



## Ventile de inchidere cu membrana

Model	Cod Danfoss	Conexiuni		Debit $k_v$ m <sup>3</sup> /h	Dimensiuni mm	
		SAE	Sudat mm		lungime	inaltime
BML 6	9G0101	1/4"	-	0,30	66	65
BML 10	9G0127	3/8"	-	0,84	72	65
BML 12	9G0141	1/2"	-	1,50	88	74
BML 15	9G0168	5/8"	-	2,20	106	86
BML 6 S	9G0108	-	6	0,30	65	63
BML 10 S	9G0128	-	10	0,84	72	65
BML 12 S	9G0148	-	12	1,50	87	74
BML 15 S	9G0170	-	15	2,20	106	86
BML 18 S	9G0184	-	18	2,90	103	89
BML 22 S	9G0194	-	22	2,90	103	89
BML 6 S	9G0208	-	6 (stut)	0,30	117	65
BML 10 S	9G0228	-	10 (stut)	0,84	117	65
BML 12 S	9G0248	-	12 (stut)	1,50	127	74
BML 15 S	9G0262	-	15 (stut)	2,20	165	86
BML 22 S	9G0291	-	22 (stut)	2,90	181	89

Presiune maxima de lucru 28bar

Domeniu de lucru -temperatura : -55...+100°C

Modelele BML sunt cu racord cu filet

Modelele BMLS sunt cu racord sudat