



Ventile magnetice

Model	Conexiuni		D. nom. scaun mm
	filet SAE	sudabil	
1020/2	1/4"	-	2,5
1028/2	-	1/4"	2,2
1028/M10	-	10 mm	3
1020/3	3/8"	-	
1064/3	3/8"	-	7
1068/3	-	3/8"	
1068/M10	-	10 mm	
1068/M12	-	12 mm	
1064/4	1/2"	-	
1070/4	1/2"	-	12,5
1078/4	-	1/2"	
1078/M12	-	12 mm	
1070/5	5/8"	-	
1078/5	-	5/8", 16 mm	
1070/6	1 1/16" UNF	-	-
1078/6	-	18 mm	
1078/7	-	22 mm	
1079/7	-	7/8", 22 mm	25,5
1078/9	-	1 1/8"(28mm)	
1079/11	-	1 3/8", 35 mm	
1098/7	-	7/8", 22 mm	16,5
1099/9	-	1 1/8"(28mm)	
1098/9	-	1 1/8"(28mm)	25
1099/11	-	1 3/8", 35 mm	
1078/11	-	1 3/8", 35 mm	27
1079/13	-	1 5/8"	
1079/M42	-	42 mm	

- presiune maxima de lucru: 30 bar
- temperatura ambienta: -35...+110°C

Bobine

Model	Alimentare	Putere
HM2 9100/RA2	24 V A.C.	8 W
HM2 9100/RA6	220/230 V	8 W
HM2 9100/RA8	380 V	8 W
HM3 9120/RD1	12 V D.C.	8 W
HM3 9120/RD2	24 V D.C.	8 W

Conector electric

Model	Alimentare
9150/R02	220 V