

S.C. Kubitech S.R.L.
700268 Iași, Bd. Socola 57, bl. A1, RO 8508803, J22/874/1996
T/F: 0232 257.555, contact@kubitech.ro, www.kubitech.ro
RO39 BPOS 2400 2831 438R OL01 - Bancpost Iași



Kubitech
tehnică de frig



Ventile sens unic

Ventile sens unic cu racord cu filet

Model	Conexiune filet SAE	Debit k_v m ³ /h	Cadere de presiune bar
3110/2	1/4"	0,40	0,10
3110/3	3/8"	1,60	0,10
3110/4	1/2"	1,80	0,10
3110/5	5/8"	3,30	0,10
3110/6	1 1/16" UNF	3,30	0,10

Ventile sens unic cu stut sudat

Model	Conexiune sudabil	Debit k_v m ³ /h	Cadere de presiune bar
3130/2	1/4"	0,50	0,10
3130/3	3/8"	1,60	0,10
3130/M10	10 mm	1,60	0,10
3130/M12	12 mm	1,80	0,10
3130/4	1/2"	1,80	0,10

3130/5	5/8"	3,30	0,10
3130/M18	18 mm	3,30	0,10
3130/6	3/4"	3,30	0,10

Ventile sens unic cu racord sudat

Model	Conexiune sudabil	Debit k_v m ³ /h	Cadere de presiune bar
3122/7	7/8"	6,60	0,10
3122/9	1 1/8"	8,80	0,10
3122/11	1 3/8"	15,20	0,10
3122/13	1 5/8"	25,00	0,10
3122/M42	42 mm	25,00	0,10
3122/17	2 1/8"	40,00	0,10

- presiune maxima de lucru: 30 bar

- temperatura ambianta: -40... +120°C



Ventile sens unic

Ventile sens unic cu racord cu filet

Model	Cod Danfoss	Conexiune filet	Debit k_v m ³ /h	Cadere de presiune bar
NRV 6	20-1040	1/4" SAE	0,56	0,07
NRV 10	20-1041	3/8" SAE	1,43	0,07
NRV 12	20-1042	1/2" SAE	2,05	0,05

NRV 16	20-1043	5/8" SAE	3,60	0,05
NRV 19	20-1044	1 1/16" UNF	5,50	0,05

Ventile sens unic cu racord sudat

Model	Cod Danfoss	Conexiune sudabil	Debit k_v m ³ /h	Cadere de presiune bar
NRV 6s	20-1014	6 mm	0,56	0,07
NRV 6s	20-1050	10 mm	0,56	0,07
NRV 10s	20-1015	10 mm	1,43	0,07
NRV 10s	20-1051	12 mm	1,43	0,07
NRV 12s	20-1016	12 mm	2,05	0,05
NRV 12s	20-1052	16 mm	2,05	0,05
NRV 16s	20-1018	16 mm	3,60	0,05
NRV 16s	20-1053	18 mm	3,60	0,05
NRV 19s	20-1017	18 mm	5,50	0,05
NRV 19s	20-1054	22 mm	5,50	0,05
arc intarit (simbol albastru)				
NRVH 6s	20-1062	10 mm	0,56	0,30
NRVH 10s	20-1036	10 mm	1,43	0,30
NRVH 10s	20-1063	12 mm	1,43	0,30
NRVH 12s	20-1037	12 mm	2,05	0,30
NRVH 12s	20-1064	16 mm	2,05	0,30
NRVH 16s	20-1038	16 mm	3,60	0,30
NRVH 16s	20-1065	18 mm	3,60	0,30
NRVH 19s	20-1008	18 mm	5,50	0,30
NRVH 19s	20-1066	22 mm	5,50	0,30

- presiune maxima de lucru: 28 bar

- temperatura ambianta: -50... +140°C



Model	Cod Danfoss	Conexiune sudabil	Debit k_v m ³ /h	Cadere de presiune bar
NRV 22s	20-1020	22 mm	8,5	0,04
NRV 22s	20-1055	28 mm	8,5	0,04
NRV 28s	20-1025	28 mm	19,0	0,04
NRV 28s	20-1056	35 mm	19,0	0,04
NRV 35s	20-1026	35 mm	29,0	0,04
NRV 35s	20-1027	42 mm	29,0	0,04
NRVH 22s	20-1032	22 mm	8,5	0,30
NRVH 22s	20-1067	28 mm	8,5	0,30
NRVH 28s	20-1033	28 mm	19,0	0,30
NRVH 28s	20-1068	35 mm	19,0	0,30
NRVH 35s	20-1034	35 mm	29,0	0,30
NRVH 35s	20-1035	42 mm	29,0	0,30

- presiune maxima de lucru: 28 bar
- temperatura ambianta: -50... +140°C