

S.C. Kubitech S.R.L.
 700268 Iași, Bd. Socola 57, bl. A1, RO 8508803, J22/874/1996
 T/F: 0232 257.555, contact@kubitech.ro, www.kubitech.ro
 RO39 BPOS 2400 2831 438R OL01 - Bancpost Iași



Kubitech
 tehnică de frig



Vizoare curgere cu si fara indicator umiditate

Model	Conexiuni		Caracteristici
	filet SAE	sudabil mm	
3610 /22	1/4"	-	filetare ext. x filetare ext.
3610 /33	3/8"		
3610 /44	1/2"		
3610 /55	5/8"		
3610 /66	1" UNF		
3640 /2	1/4"	-	lipire int. x lipire int.
3640 /3	3/8"	-	
3640 /M10	-	10	
3640 /M12	-	12	
3640 /4	1/2"	-	
3640 /5	5/8"	-	
3640 /M18	-	18	
3640 /6	3/4"	-	
3640 /7	7/8"	-	
3640 /9	1 1/8"	-	

3650 /22	1/4"	-		filetare ext. x filetare int.
3650 /33	3/8"			
3650 /44	1/2"			
3650 /55	5/8"			
3650 /66	1" UNF			
3710 /22	1/4"	-		filetare ext. x filetare ext.
3710 /33	3/8"			
3710 /44	1/2"			
3710 /55	5/8"			
3710 /66	1" UNF			
3740 /2	1/4"	-	Cu indicator de umiditate	lipire int. x lipire int.
3740 /3	3/8"	-		
3740 /M10	-	10		
3740 /M12	-	12		
3740 /4	1/2"	-		
3740 /5	5/8"	-		
3740 /M18	-	18		
3740 /6	3/4"	-		
3740 /7	7/8"	-		
3740 /9	1 1/8"	-		
3760 /9	1 1/8"	-		lipire int. x lipire int. prevazut cu 2 vizoare
3760 /11	1 3/8"			
3760 /13	1 5/8"			
3750 /22	1/4"	-		filetare ext. x filetare int.
3750 /33	3/8"			
3750 /44	1/2"			
3750 /55	5/8"			
3750 /66	1" UNF			

Temperatura maxima de lucru este: pentru modelele cu indicator de +70°C

pentru modelele fara indicator de +110°C

Presiunea maxima de lucru este de 35 bar.